

Exam Number/Code: 1Z0-580

Exam Name: Oracle Solaris 11
Installation and Configuration Essentials

Version: Demo

<http://www.it-exams.com>

QUESTION NO: 1

What information would the "beadm list -ds" command output?

- A. a list of all Bes
- B. a list of the datasets and snapshot information for the active BE
- C. a list of the datasets and snapshot information for all Bes
- D. a list of the default sets
- E. a list of BEs in machine readable format

Answer: C

Explanation:

You can display information about snapshots, boot environments, and datasets that were created by the beadm command by using the beadm list subcommand. The beadm list command output also displays boot environments that are created by the pkg command.

The beadm list command syntax is:

Syntax: beadm list [-a | [-ds] [-H] [BeName]

The command lists information about the existing boot environment. To view information for a specific boot environment, replace BeName with a boot environment name. If a specific boot environment is not specified, the command lists information about all boot environments. The default is to list boot environments without additional information.

-a – Lists all available information about the boot environment. This information includes subordinate datasets and snapshots.

-d – Lists information about all subordinate datasets that belong to the boot environment.

-s – Lists information about the snapshots of the boot environment.

-H – Prevents listing header information. Each field in the output is separated by a semicolon.

Reference:Oracle Solaris 11 Information Library,Listing Existing Boot Environments and Snapshots

QUESTION NO: 2

Which two statements are true of the GRUB menu?

- A. GRUB is the default boot loader for Oracle Solaris 11 SPARC and x86.
- B. GRUB supports Oracle Solaris and Oracle Linux only.
- C. GRUB loads akernel based upon the file name, disk, and partition specified.
- D. GRUB uses boot environments for all operating systems.
- E. GRUB is fully compliant with the Multiboot specification.

Answer: A,C

QUESTION NO: 3

A developer wants to use DTrace in a zone to examine the kernel. What are his options?

- A. Modify the zone so that he can use DTrace to examine kernel data structures.
- B. All that's required is to assume the "root" role.
- C. By using `dtrace_proc` and `dtrace_user` privileges he can examine his own code, but not the kernel.
- D. By adding `ipc_dac_read` and `ipc_dac_write` privileges to the zone.
- E. Change the zone's file-mac-profile from `strict` to `none` to enable the use of DTrace within the zone.

Answer: C

Explanation: How to Use DTrace in a Non-global Zone

```
global# zonecfg -z my-zone
zonecfg:my-zone> set limitpriv="default,dtrace_proc,dtrace_user"
zonecfg:my-zone> exit
```

Note –

Depending on your requirements, you can add either privilege, or both privileges.

Log in to the zone.

```
global# zlogin my-zone
my-zone# dtrace -l
```

Note:

*Oracle Solaris DTrace is a comprehensive, advanced tracing tool for troubleshooting systemic problems in real time.

*DTrace helps you understand a software system by enabling you to dynamically modify the operating system kernel and user processes to record additional data that you specify at locations of interest, called probes.

Reference: System Administration Guide: Oracle Solaris Containers-Resource Management and Oracle Solaris Zones, Using DTrace in a Non-Global Zone

QUESTION NO: 4

Your system has two disk devices, `c2t0d0` and `c2t1d0`, and two flash devices, `c2t5d0` and `c2t8d0`.

Which command would you use to create a storage pool named "tank," which mirrors the disks and adds the two flash devices as "cache"?

- A. `zpool create tank mirror c2t0d0 c2t1d0 mirror c2t5d0 c2t8d0`
- B. `zpoolcreate tank mirror c2t0d0 c2t1d0 log mirrorc2t5d0 c2t8d0`
- C. `zpool c2t0d0 c2t1d0 cachec2t5d0 c2t8d0mirror`
- D. `zpool create tank mirror c2t0d0 c2t1d0 cachec2t5d0 c2t8d0`
- E. `zpool create tankraidz2c2t0d0 c2t1d0 c2t5d0 c2t8d0`

Answer: D

Explanation:

Creating a ZFS Storage Pool with Cache Devices

You can create a storage pool with cache devices to cache storage pool data. For example:

```
# zpool create tank mirror c2t0d0 c2t1d0 c2t3d0 cache c2t5d0 c2t8d0
```

Note:

*Creating a Basic Storage Pool

The following command creates a new pool named tank that consists of the disks c1t0d0 and c1t1d0:

```
#zpool status tank
```

```
pool: tank
```

```
state: ONLINE
```

```
scrub: none requested
```

```
config:
```

```
NAME STATE READ WRITE CKSUM
```

```
tank ONLINE 0 0 0
```

```
mirror-0 ONLINE 0 0 0
```

```
c2t0d0 ONLINE 0 0 0
```

```
c2t1d0 ONLINE 0 0 0
```

```
c2t3d0 ONLINE 0 0 0
```

```
cache
```

```
c2t5d0 ONLINE 0 0 0
```

```
c2t8d0 ONLINE 0 0 0
```

```
errors: No known data errors
```

```
# zpool create tank c1t0d0 c1t1d0
```

These whole disks are found in the /dev/dsk directory and are labelled appropriately by ZFS to contain a single, large slice. Data is dynamically striped across both disks.

*Creating a Mirrored Storage Pool

To create a mirrored pool, use the mirror keyword, followed by any number of storage devices that will comprise the mirror. Multiple mirrors can be specified by repeating the mirror keyword on the command line. The following command creates a pool with two, two-way mirrors:

```
# zpool create tank mirror c1d0 c2d0 mirror c3d0 c4d0
```

Reference:Solaris ZFS Administration Guide,Creating a ZFS Storage Pool with Cache Devices

QUESTION NO: 5

The "pkg update" command will _____.

- A. update all packages that have updates available including the kernel
- B. update all packages that have updates available excluding the kernel

- C. update only the kernel image
- D. update the global zone packages and non-global zone packages
- E. update all packages and the kernel, and then automatically reboot the system

Answer: A

Explanation: Updating all of the packages on your installed system – To update all of the packages on your system that have available updates, use the pkg update command, as follows:

```
# pkg update
```

Running this command updates packages that you might not otherwise consider updating, for example, kernel components and other low-level system packages.

QUESTION NO: 6

What three items are true with regard to network planning in a Solaris 11 environment?

- A. Hardware and network topology should be planned in advance of installation.
- B. Subnetting needs to be considered when implementing IPv6 networks.
- C. IPv4 and IPv6 network addressing cannot co-exist on the same server.
- D. Solaris 11 enables the use of local files, NIS, DNS, or LDAP for name services.
- E. The physical network topology will determine if you need routers, not all networks require routers.

Answer: A,C,D

Explanation:

The following table lists different tasks for planning the network configuration.

* (A) Identify the hardware requirements of your planned network topology.

Determine the types of equipment that you need for your network site.

* (C) Determine the type of IP addresses to use and obtain registered IP addresses.

Select whether you are deploying a purely IPv4 network, an IPv6 network, or a network that uses both types of IP addresses. Obtain unique IP addresses to communicate to public networks in the Internet.

* (D) Determine a naming scheme to identify the hosts in the network as well as the name service to use.

Create a list of names to assign to the systems on the network and decide whether to use NIS,

LDAP, DNS, or the network databases in the local /etc directory.

* If necessary, establish administrative subdivisions and design a strategy for subnets.

Decide if your site requires that you divide your network into subnets to service administrative subdivisions

* Determine where to place routers in the network design.

If your network is large enough to require routers, create a network topology that supports them.

*Decide whether to create virtual networks in the overall network configuration scheme. You might need to create virtual networks within a system to reduce the hardware footprint of your network.

Reference:Oracle Solaris 11 Information Library,Network Planning (Task Map)

QUESTION NO: 7

To upgrade a system from Oracle Solaris 10 to Oracle Solaris 11, it is necessary to_____.

- A. convert all Oracle Solaris 10 packages to Oracle Solaris 11 packages using IPS
- B. use IPS and Live Upgrade to install all updated software
- C. use IPS to replace the Oracle Solaris 10 kernel with the Oracle Solaris 11 kernel
- D. save userdata and perform a new Oracle Solaris 11 install; there is no upgrade method
- E. update Oracle Solaris 10 from an Oracle Solaris 11 repository

Answer: D

Explanation:

There are no upgrade methods or tools available to transition from Oracle Solaris 10 to Oracle Solaris 11. You cannot use an installer to upgrade from Oracle Solaris 10 to Oracle Solaris 11.

Oracle Solaris 11 Transition Tools and Features

Note:

*There are no upgrade methods or tools available to transition from Oracle Solaris 10 to Oracle Solaris 11. You cannot use an installer to upgrade from Oracle Solaris 10 to Oracle Solaris 11.

/JumpStart Migration Utility (js2ai)

Used to convert Oracle Solaris 10 JumpStart rules and profiles to a format that is compatible with AI manifest entries.

/ZFS shadow migration feature

Used to migrate data from an existing file system to a new file system.

/Oracle Solaris 11 support for Oracle Solaris 10 zones

Used to migrate your Oracle Solaris 10 application environments to an Oracle Solaris 11 system.

/NFS file sharing and pool migration

Used to access shared files from an Oracle Solaris 10 system on an Oracle Solaris 11 system.

Used to import a ZFS storage pool from an Oracle Solaris 10 system into an Oracle Solaris 11 system.

Reference:Oracle Solaris 11 Information Library,Transitioning Your Oracle Solaris 10 System to Oracle Solaris 11

QUESTION NO: 8

When attempting to perform an installation of Oracle Solaris 11, you encounter a failure message along the lines of "no offers were received." What is the most likely reason for this message and why?

- A. The system could not obtain a DHCP-based lease so it could not proceed.
- B. The amount of disk space offered by the installer is inadequate so the installer attempted to compress data in memory.
- C. The minimum amount of memory is not sufficient to load the necessary network driver so the installer tried to offer disk as backing store.
- D. An IP address provided is located on a different network segment because the correct RARP server did not respond.
- E. The IP address provided is outside the range of allocatable addresses.

Answer: A

Explanation:

No DHCP or Proxy DHCP Offers Were Received

If a DHCP server is not responding to an x86 client's request, you see the following messages:

Intel(R) Boot Agent PXE Base Code (PXE-2.1 build 0.86)

Copyright(C) 1997-2007, Intel Corporation

CLIENT MAC ADDR 00 14 4F 29 04 12 GUID FF2000008 FFFF FFFF FFFF
7BDA264F1400

DHCP..... No DHCP or Proxy DHCP offers were received

PXE-MOF: Exiting Intel Boot Agent

The timeout message indicates that the client is sending a DHCP request and not getting a response. This issue is probably due to an error in the DHCP configuration. Check to see if your client is configured correctly in the DHCP server.

Reference: Oracle Solaris 11, No DHCP or Proxy DHCP Offers Were Received

QUESTION NO: 9

What are the three properties of a business critical cloud infrastructure?

- A. service isolation
- B. flexible, virtual application instances
- C. dedicated, single purpose file servers
- D. easy, intuitive provisioning, chargeback, and capacity planning
- E. rigid, inflexible network design

Answer: A,B,D

Explanation:

Oracle Cloud Infrastructure

Overview

*Flexible cloud infrastructure supports dynamic resource pooling, elastic scalability, and rapid application deployment

*Includes Oracle Enterprise Manager, a complete cloud lifecycle management solution that allows you to quickly set up, manage, and support enterprise clouds and traditional Oracle IT environments from applications to disk

*Built-in security and high availability

*Application-aware virtualization and management capabilities

QUESTION NO: 10

Which two actions must be taken to enable IP forwarding on all interfaces yet disable on a specific interface?

- A. routeadm -r
- B. ipadm set-addrprop
- C. ipadm set-ifprop
- D. routeadm -e
- E. dladm set-router

Answer: A,E

Explanation:

The routeadm command is used to administer system-wide configuration for IP forwarding and routing. IP forwarding is the passing of IP packets from one network to another; IP routing is the use of a routing protocol to determine routes.

-e option...

Enable the specified option. The effect is to prepare the associated services (svc:/network/ipv4-forwarding:default in the case of ipv4-forwarding) for enabling. By means of the routing-svcs variable, the routing daemons are specified to be enabled on subsequent boot or when routeadm - u is run.

-d option...

Disable the specified option. The effect is to prepare the associated services (svc:/network/ipv4-forwarding:default in the case of ipv4-forwarding) for enabling. By means of the routing-svcs variable, the routing daemons are specified to be disabled on subsequent boot or when routeadm-u is run.

Reference: System Administration Commands, routeadm