

Exam Number/Code:CPP

Exam Name:C++ Certified
Professional Programmer

Version: Demo

<http://www.it-exams.com>

QUESTION NO: 1

What happens when you attempt to compile and run the following code?

```
#include <iostream>
#include <set>
#include <vector>
using namespace std;
int main(){
int t[] = { 3, 4, 2, 1, 6, 5, 7, 9, 8, 0 };
vector<int>v(t, t+10);
multiset<int> s1(v.begin(),v.end());
s1.insert(v.begin(),v.end());
pair<multiset<int>::iterator,multiset<int>::iterator> range;
range = s1.equal_range(6);
while (range.first != range.second) {
cout<<*range.first<<" "; range.first++;
}
return 0;
}
```

- A. program outputs: 6 6
- B. program outputs: 5 7
- C. program outputs: 5 5 6 6 7 7
- D. program outputs: 5 5 7 7
- E. program outputs: 1 1 6 6 5 5

Answer: A

QUESTION NO: 2

What happens when you attempt to compile and run the following code?

```
#include <vector>
#include <iostream>
#include <algorithm>
using namespace std;
template<class T>struct Out {
ostream & out;
Out(ostream & o): out(o){}
void operator()(const T & val ) {
out<<val<<" ";
}
};
struct Sequence {
int start;
Sequence(int start):start(start){}
```

```

int operator()() {
return start++ ; };
int main() {
vector<int> v1(10);
generate(v1.rbegin(), v1.rend(), Sequence(1));
rotate(v1.begin(),v1.begin() + 1, v1.end() );
for_each(v1.begin(), v1.end(), Out<int>(cout) );cout<<endl;
return 0;
}

```

Program outputs:

- A. 1 2 3 4 5 6 7 8 9 10
- B. 10 9 8 7 6 5 4 3 2 1
- C. 9 8 7 6 5 4 3 2 1 10
- D. 1 10 9 8 7 6 5 4 3 2

Answer: C

QUESTION NO: 3

What happens when you attempt to compile and run the following code?

```

#include <iostream>
#include <fstream>
#include <string>
#include <list>
#include <algorithm>
#include <iomanip>
using namespace std;
class B { int val;
public:
B(int v=0):val(v){}
int getV() const {return val;}
operator int() const { return val; };};
template<class T>struct Out {
ostream & out;
Out(ostream & o): out(o){}
void operator() (const T & val ) {out<<setw(3)<<hex<<val; } };
int main () {
int t[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
fstream f("test.out", ios::trunc|ios::out);
list<B> l(t, t+10);
for_each(l.begin(), l.end(), Out<B>(f));
f.close();
f.open("test.out");
}

```

```
for( ; f.good() ; ) {  
    B i;  
    f>>i;  
    cout<<i<<" ";  
}  
f.close();  
return 0;  
}
```

- A. file test.out will be opened writing
- B. file test.out will be truncated
- C. file test.out will be opened for reading
- D. compilation error
- E. program will display sequence 1 2 3 4 5 6 7 8 9 10

Answer: D

QUESTION NO: 4

What will happen when you attempt to compile and run the code below, assuming that you enter the following sequence: one two three<enter>?

```
#include <iostream>  
#include <string>  
using namespace std;  
int main ()  
{  
    string a;  
    cin>>a;  
    cout<<a<<endl;  
    return 0;  
}
```

Program will output:

- A. one
- B. one two three
- C. runtime exception
- D. compilation error
- E. the result is unspecified

Answer: A

QUESTION NO: 5

What will happen when you attempt to compile and run the following code?

```

#include <iostream>
#include <map>
#include <vector>
#include <sstream>
#include <string>
using namespace std;
int main() {
int t[] = { 3, 4, 2, 1, 0, 3, 4, 1, 2, 0 };
vector<int> v(t, t + 10);
multimap<int, string> m;
for (vector<int>::iterator i = v.begin(); i != v.end(); i++) {
stringstream s;s << *i << *i;
m.insert(pair<int, string>(*i, s.str()));
}
pair<multimap<int, string>::iterator, multimap<int, string>::iterator> range;
range = m.equal_range(2);
for (multimap<int, string>::iterator i = range.first; i != range.second; i++) {
cout << i->first << " ";
}
return 0;
}

```

The output will be:

- A. 2 2
- B. 1 2
- C. 1 3
- D. 2
- E. 0 2

Answer: A