Exam Number/Code :   HP0-J46

Exam Name :   Designing and Implementation HP Enterprise Backup Solution

Version :   Demo

QUESTION NO: 1
Which device is the bottleneck in an EBS environment with optimum performance?
A. switch
B. server
C. primary storage
D. tape drive
Answer: D

QUESTION NO: 2
You are implementing a D2D4100 array with deduplication. What can you do to increase the backup performance?
A. Set the device blocksize as low as possible.
B. Set the segment size to 2GB.
C. Set the host concurrency parameter in the backup application to its maximum.
D. Set the device concurrency parameter in the backup application to 1.
Answer: D

QUESTION NO: 3
Which component in a Symantec NetBackup solution is responsible for scheduling and tracking client backups?
A. Media Server
B. Cell Server
C. Master Server
D. Storage Manager
Answer: C

QUESTION NO: 4
What must you do with Emulex HBAs connected to fabric switches when implementing an EBS solution? (Select two.)
A. Install them in the last PCI slots of each server.
B. Ensure that all entries in the registry for the HBAs are set to 0.
C. Verify that the topology adapter parameter is set to 1.
D. Disable any unused ports.
E. Verify that the link speed is the same for the HBA and the connected SAN switch port.
Answer: C,E

QUESTION NO: 5
Which best practice should be followed when configuring a Virtual Library System 9000 for backup in an EBS environment?
A. Enable software and hardware compression to increase performance.
B. Use small cartridges to raise thededuplication ratio.
C. Use Echo Copy to mirror backups within the VLS.
D. Use ten characters when creating barcode labels to support all backup ISVs.
Answer: B

QUESTION NO: 6

An administrator wants to manage and share devices across multiple cells in an HP Data Protector environment. Which component must be installed in an EBS solution?

A. Central Management Console

B. Manager-of-Managers

C. Centralized User Interface

D. Shared Library option

Answer: B