

Exam Number/Code:HP5-T01D

Exam Name:Delta - Supporting HP
Industry Standard Server Solutions

Version: Demo

<http://www.it-exams.com>

QUESTION NO: 1

Where can you verify the status of an external DVD-ROM drive in a c7000 enclosure?

- A. Active Health Log
- B. Integrated Management Log
- C. Virtual SAS Manager
- D. Insight Display

Answer: D

QUESTION NO: 2

What should be installed on a ProLiant Gen8 server to display operating system information within the iLO 4 GUI?

- A. HP Management Agents
- B. System Management Home Page
- C. Agentless Management Service
- D. ProLiant Support Pack

Answer: C

Reference:

<http://h20000.www2.hp.com/bc/docs/support/SupportManual/c03488111/c03488111.pdf>

QUESTION NO: 3

Which button should you press to enter the RBSU during POST?

- A. F8
- B. F9
- C. F11
- D. F12

Answer: B

Reference:<http://h20000.www2.hp.com/bizsupport/TechSupport/Document.jsp?objectID=c03255924&prodSeriesId=5177953>(See Using RBSU)

QUESTION NO: 4

Which steps should you perform to save a Virtual Connect configuration?

- A. enclosure setting, configuration scripts, show config, save
- B. enclosure setting, configuration scripts, inventory
- C. from CLI: show all > cfg.txt
- D. VCM, Tools, Backup/Restore Domain Configuration

Answer: A

QUESTION NO: 5

Why should you use an electrostatic discharge (ESD) wrist strap when replacing parts such as memory DIMMs?

- A. It prevents the part from being damaged by static electricity.
- B. It incorporates high resistance and dissipates electrical charges into the ozone.
- C. A 48 V DC PSU will contribute to higher static electricity.
- D. A current of more than 75 mA can kill someone.

Answer: A

QUESTION NO: 6

You replaced a Smart Array P812 in a ProLiant DL380 G7 storage server. What should you do next?

- A. Check the FBWC charge.
- B. Replace the cache module.
- C. Install the BBWC battery.
- D. Verify that the firmware level is current.

Answer: D